

SAT GLASS



Ventilazione Frontale (1 Motore) - Uscita Fumi Posteriore

Front Ventilation (1 Motor) - Rear Exhaust Fume Outlet - Ventilación Frontal (1 Motor) - Salida De Humos Trasera - Ventilation Avant (1 Moteur) - Sortie De Fumée Arrière - Front Gebläse (1 Motor) - Rauchausgang Hinten



Corten

Petrol
Petroleum - Huile -
Acete - Öl

Bianco
White - Blanc - Bianco
- Weiß

Nero
Black - Noir - Negro -
Schwarz

Bordeaux
Bordeaux - Bordeaux
Bordeaux - Bordeaux

TECHNOLOGY



OPTIONAL



Potenza Globale
Global Power
Puissance globale
Potencia global
Verdennungsleistung

Potenza Nominale
Nominal Power
Puissance Nominale
Potencia Nominal
Nennleistung

Rendimento totale
Total efficiency
Puissance globale
Potencia global
Pellet Wirkungsgrad

Peso
Weight
Poids
Peso
Gewicht

Consumo min-MAX
Min-Max consumption
Consumation min-MAX
Consumo min-maxi
Min-Maxi Verbrauch

Temperatura gas di scarico
Exhaust gas temperature
Température des gaz d'échappement
Temperatura de los gases de escape
Abgastemperatur

Tiraggio richiesto in funzionamento
Draw required in operation
Dessiner nécessaire en fonctionnement
Dibujar requerido en la operación
Erforderlicher Betriebszug

Uscita fumi
Chimney Output
Sortie conduit de cheminée
Salida conducto de humos
Rauchauslass

Ingresso aria
Air inlet
Entrée d'air
Entrada aire
Lufteinlass

Serbatoio pellet
Pellet tank
Dépôt
Depósito
Tank Fassungsvermögen

Assorbimento elettrico watt
Electrical consumption watt
Absorption électrique watt
Consumo de electricidad watt
Elektrischer Verbrauch watt

A 7	KW 8	KW 7,0-2,5	% 88,3	Kg 110	Kg/H 0,6-1,6	°C 189,5	Pa 3	mm 80	mm 60	Kg 15	M270-N46-R28
------------	-------------	-------------------	---------------	---------------	---------------------	-----------------	-------------	--------------	--------------	--------------	---------------------

